

BILATERAL FIT REPORT: FIT MEASUREMENTS


Retul, Muve

Power: 100 Watts

Left Notes: -

Right Notes:


SADDLE POSITION

	L	R		L	R
	-	Ankle Angle at Bottom 92 °		-	Knee Angle Flexion 105 °
				-	Knee Angle Extension 40 °
	-	Knee Forward of Spindle -		-	Hip Vertical Travel 55 mm
	-	Hip Lateral Travel 19 mm		-	Foot Rotation Mean -15 °
	-	Cadence Average 89		-	Knee Forward of Foot 86 mm

HANDLEBAR POSITION

	L	R		L	R
	-	Shoulder Angle to Elbow 77 °		-	Back Angle 24 °
	-	Shoulder Angle to Wrist 116 °			
	-	Hip Angle Closed 51 °		-	Elbow Angle 88 °
	-	Forearm Angle 14 °		-	Cadence Average 89

PEDALING ALIGNMENT

L		R		L		R	
	- Knee Lateral Travel	36 mm			- Hip Vertical Travel	55 mm	
	- Hip Lateral Travel	19 mm			- Hip to Foot Lateral Offset	-30 mm	
	- Knee to Foot Lateral Offset	22 mm			- Knee Travel Tilt	7 °	
	- Foot Rotation Mean	-15 °			- Cadence Average	89	

WORKLOAD

L		R	
	- Cadence Mean	89	
	- Cadence Maximum	99	

MARKER PATH

Note: Marker paths viewed from the front will be on the opposite side of the report. The paths representing the right side of the body will be shown on the left and vice versa.



Front View of Right Knee Path:



Front View of Left Knee Path:

No Knee Trace Image



Bike Frame

